

SAFETY DATA SHEET

BIODUR®

according to Commission Regulation (EU) 2020/878 as amended

BIODUR ACRYLIC PRIMER

Creation date 28th March 2023
Revision date Version 1.0

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier BIODUR ACRYLIC PRIMER

Substance / mixture mixture

UFI J800-F0TW-A00T-T32U

1.2. Relevant identified uses of the substance or mixture and uses advised against

Mixture's intended use

Primer universal for preparation for painting metal, wood, glass, stone, brick and some types of plastic surfaces. Fills in scratches and cavities. Makes strong protective coat ready for polishing 30 min after application. Primered surface is resistant to mechanical and weather effects.

Main intended use

PC-PNT-1 Aerosol paints and coatings

Mixture uses advised against

The product should not be used in ways other than those referred in Section 1.

1.3. Details of the supplier of the safety data sheet

Importer

Name or trade name BIODUR Sp. z o. o.
Address ul. Modlińska 6a, lok. 224 , Warszawa, 03-216
Poland
Identification number (CRN) 6762484086
VAT Reg No PL6762484086
Phone +48123766552
E-mail info@biodur.pl
Web address www.biodur.pl

Manufacturer

Name or trade name "NEWTON-PROMSERVICE" LLC
Address App. 110 Chichibabina., 9, app. 110, , Charkiw
Ukraine
Phone 0800-31-34-85
E-mail e-marketing@newton.ua
Web address newton.ua

Competent person responsible for the safety data sheet

Name BIODUR Sp. z o. o.
E-mail info@biodur.pl

1.4. Emergency telephone number

European emergency number: 112

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification of the mixture in accordance with Regulation (EC) No 1272/2008

The mixture is classified as dangerous.

Aerosol 1, H229, H222
Skin Irrit. 2, H315
Eye Irrit. 2, H319
STOT SE 3, H336

Full text of all classifications and hazard statements is given in the section 16.

Most serious adverse physico-chemical effects

Pressurised container: May burst if heated. Extremely flammable aerosol.

Most serious adverse effects on human health and the environment

Causes serious eye irritation. May cause drowsiness or dizziness. Causes skin irritation.

SAFETY DATA SHEET

BIODUR®

according to Commission Regulation (EU) 2020/878 as amended

BIODUR ACRYLIC PRIMER

Creation date 28th March 2023
Revision date Version 1.0

2.2. Label elements

Hazard pictogram



Signal word

Danger

Hazardous substances

methyl acetate

n-butyl acetate

Hazard statements

H222 Extremely flammable aerosol.
H229 Pressurised container: May burst if heated.
H315 Causes skin irritation.
H319 Causes serious eye irritation.
H336 May cause drowsiness or dizziness.

Precautionary statements

P101 If medical advice is needed, have product container or label at hand.
P102 Keep out of reach of children.
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211 Do not spray on an open flame or other ignition source.
P251 Do not pierce or burn, even after use.
P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C.

Supplemental information

EUH211 Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.
EUH066 Repeated exposure may cause skin dryness or cracking.
Density 0,75-1,20 г/см³ при 20 °C
VOC limit value cat. B (c) : 780 g/l

2.3. Other hazards

The mixture does not contain substances with endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605. Mixture does not contain any substance meet the criteria for PBT or vPvB in accordance with Annex XIII of Regulation (EC) No. 1907/2006 (REACH) as amended.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Mixture contains these hazardous substances and substances with the highest permissible concentration in the working environment

| Identification numbers | Substance name | Content in % weight | Classification according to Regulation (EC) No 1272/2008 | Note |
|--|----------------|---------------------|---|------|
| Index: 601-003-00-5 CAS: 74-98-6 EC: 200-827-9 | propane | ≤35,0 | Flam. Gas 1, H220 Press. Gas (compressed gas), H280 | 2 |
| Index: 607-021-00-X CAS: 79-20-9 EC: 201-185-2 | methyl acetate | ≤30,0 | Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336 EUH066 | |

SAFETY DATA SHEET

BIODUR®

according to Commission Regulation (EU) 2020/878 as amended

BIODUR ACRYLIC PRIMER

Creation date 28th March 2023
Revision date Version 1.0

| Identification numbers | Substance name | Content in % weight | Classification according to Regulation (EC) No 1272/2008 | Note |
|---|-----------------|---------------------|---|------|
| Index: 601-004-00-0 CAS: 106-97-8 EC: 203-448-7 | butane | ≤15,0 | Flam. Gas 1, H220 Press. Gas (compressed gas), H280 | 1, 2 |
| Index: 607-022-00-5 CAS: 141-78-6 EC: 205-500-4 | ethyl acetate | ≤15 | Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336 EUH066 | 3 |
| Index: 607-025-00-1 CAS: 123-86-4 EC: 204-658-1 | n-butyl acetate | ≤10,0 | Flam. Liq. 3, H226 STOT SE 3, H336 EUH066 | 3 |

Notes

- Note C: Some organic substances may be marketed either in a specific isomeric form or as a mixture of several isomers. In this case the supplier must state on the label whether the substance is a specific isomer or a mixture of isomers.
- Note U (Table 3): When put on the market gases have to be classified as "Gases under pressure", in one of the groups compressed gas, liquefied gas, refrigerated liquefied gas or dissolved gas. The group depends on the physical state in which the gas is packaged and therefore has to be assigned case by case. The following codes are assigned:

Press. Gas (Comp.)
Press. Gas (Liq.)
Press. Gas (Ref. Liq.)
Press. Gas (Diss.)

Aerosols shall not be classified as gases under pressure (See Annex I, Part 2, Section 2.3.2.1, Note 2).

- A substance for which exposure limits are set.

Full text of all classifications and hazard statements is given in the section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

If any health problems are manifested or if in doubt, inform a doctor and show him information from this safety data sheet.

If inhaled

Terminate the exposure immediately; move the affected person to fresh air. Protect the person against growing cold. Provide medical treatment if irritation, dyspnoea or other symptoms persist.

If on skin

Remove contaminated clothes. Wash the affected area with plenty of water, lukewarm if possible.

If in eyes

Rinse eyes immediately with a flow of running water, open the eyelids (also using force if needed); remove contact lenses immediately if worn by the affected person. Rinsing should continue at least for 10 minutes. Provide medical treatment, specialized if possible.

If swallowed

Unlikely.

4.2. Most important symptoms and effects, both acute and delayed

If inhaled

May cause drowsiness or dizziness.

If on skin

Causes skin irritation.

If in eyes

Causes serious eye irritation.

If swallowed

Irritation, nausea.

4.3. Indication of any immediate medical attention and special treatment needed

Symptomatic treatment.

SAFETY DATA SHEET

BIODUR®

according to Commission Regulation (EU) 2020/878 as amended

BIODUR ACRYLIC PRIMER

Creation date 28th March 2023
Revision date Version 1.0

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Alcohol-resistant foam, carbon dioxide, powder, water spray jet, water mist.

Unsuitable extinguishing media

Water - full jet.

5.2. Special hazards arising from the substance or mixture

In the event of fire, carbon monoxide, carbon dioxide and other toxic gases may arise. Inhalation of hazardous degradation (pyrolysis) products may cause serious health damage.

5.3. Advice for firefighters

Self-Contained Breathing Apparatus (SCBA) with a chemical protection suit only where personal (close) contact is likely. Use a self-contained breathing apparatus and full-body protective clothing. Closed containers with the product near the fire should be cooled with water. Do not allow run-off of contaminated fire extinguishing material to enter drains or surface and ground water.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Provide sufficient ventilation. Pressurised container: May burst if heated. Extremely flammable aerosol. Remove all ignition sources. Use personal protective equipment for work. Follow the instructions in the Sections 7 and 8. Do not inhale aerosols. Prevent contact with skin and eyes.

6.2. Environmental precautions

Prevent contamination of the soil and entering surface or ground water.

6.3. Methods and material for containment and cleaning up

Spilled product should be covered with suitable (non-flammable) absorbing material (sand, diatomaceous earth, earth and other suitable absorption materials); to be contained in well closed containers and removed as per the Section 13. In the event of leakage of the substantial amount of the product, inform fire brigade and other competent bodies. After removal of the product, wash the contaminated site with plenty of water. Do not use solvents.

6.4. Reference to other sections

See the Section 7, 8 and 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Prevent formation of gases and vapours in flammable or explosive concentrations and concentrations exceeding the occupational exposure limits. The product should be used only in the areas where it is not in contact with open fire and other ignition sources. Use non-sparking tools. Use of antistatic clothes and footwear is recommended. Do not inhale aerosols. Prevent contact with skin and eyes. No smoking. Protect against direct sunlight. Do not pierce or burn, even after use. Wash hands and exposed parts of the body thoroughly after handling. Do not spray on an open flame or other ignition source. Use only outdoors or in a well-ventilated area. Use personal protective equipment as per Section 8. Observe valid legal regulations on safety and health protection.

7.2. Conditions for safe storage, including any incompatibilities

Store in tightly closed containers in cold, dry and well ventilated areas designated for this purpose. Store locked up. Protect from sunlight. Keep container tightly closed. Do not expose to temperatures exceeding 50 °C.

| Content | Packaging type | Material of package |
|---------|----------------|---------------------|
| 500 ml | aerosol can | FE |

7.3. Specific end use(s)

not available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

The mixture contains substances for which occupational exposure limits are set.

European Union

Commission Directive (EU) 2017/164

| Substance name (component) | Type | Value |
|-------------------------------|-------------|-----------------------|
| ethyl acetate (CAS: 141-78-6) | OEL 8 hours | 734 mg/m ³ |

SAFETY DATA SHEET

BIODUR®

according to Commission Regulation (EU) 2020/878 as amended

BIODUR ACRYLIC PRIMER

Creation date 28th March 2023
Revision date Version 1.0

European Union

Commission Directive (EU) 2017/164

| Substance name (component) | Type | Value |
|-------------------------------|----------------|------------------------|
| ethyl acetate (CAS: 141-78-6) | OEL 8 hours | 200 ppm |
| | OEL 15 minutes | 1468 mg/m ³ |
| | OEL 15 minutes | 400 ppm |

European Union

Commission Directive 2000/39/EC

| Substance name (component) | Type | Value |
|---------------------------------|----------------|-----------------------|
| n-butyl acetate (CAS: 123-86-4) | OEL 8 hours | 241 mg/m ³ |
| | OEL 8 hours | 50 ppm |
| | OEL 15 minutes | 723 mg/m ³ |
| | OEL 15 minutes | 150 ppm |

8.2. Exposure controls

Follow the usual measures intended for health protection at work and especially for good ventilation. This can be achieved only by local suction or efficient general ventilation. If exposure limits cannot be observed in this mode, suitable protection of airways must be used. Do not eat, drink and smoke during work. Wash your hands thoroughly with water and soap after work and before breaks for a meal and rest.

Eye/face protection

Protective goggles.

Skin protection

Hand protection: Protective gloves resistant to the product. Contaminated skin should be washed thoroughly.

Respiratory protection

Halfmask with a filter against organic vapours or a self-contained breathing apparatus as appropriate if exposure limit values of substances are exceeded or in a poorly ventilated environment.

Thermal hazard

Not available.

Environmental exposure controls

Observe usual measures for protection of the environment, see Section 6.2.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

| | |
|--|--------------------------------------|
| Physical state | liquid |
| Colour | white, grey, black, wg asortymentu |
| Odour | data not available |
| Melting point/freezing point | data not available |
| Boiling point or initial boiling point and boiling range | data not available |
| Flammability | data not available |
| Lower and upper explosion limit | data not available |
| Flash point | data not available |
| Auto-ignition temperature | data not available |
| Decomposition temperature | data not available |
| pH | 0 (undiluted) |
| Kinematic viscosity | data not available |
| Solubility in water | data not available |
| Partition coefficient n-octanol/water (log value) | data not available |
| Vapour pressure | data not available |
| Density and/or relative density | |
| Density | 0,75-1,20 g/cm ³ at 20 °C |
| Relative vapour density | data not available |
| Particle characteristics | data not available |

9.2. Other information

VOC limit value cat. B (c) : 780 g/l

SAFETY DATA SHEET

BIODUR®

according to Commission Regulation (EU) 2020/878 as amended

BIODUR ACRYLIC PRIMER

| | | | |
|---------------|-----------------|---------|-----|
| Creation date | 28th March 2023 | Version | 1.0 |
| Revision date | | | |

SECTION 10: Stability and reactivity

10.1. Reactivity

not available

10.2. Chemical stability

The product is stable under normal conditions.

10.3. Possibility of hazardous reactions

Unknown.

10.4. Conditions to avoid

The product is stable and no degradation occurs under normal use. Protect against flames, sparks, overheating and against frost. Pressurised container: May burst if heated.

10.5. Incompatible materials

Protect against strong acids, bases and oxidizing agents.

10.6. Hazardous decomposition products

Not developed under normal uses. Dangerous outcomes such as carbon monoxide and carbon dioxide are formed at high temperature and in fire.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Inhalation of solvent vapors above values exceeding exposure limits for working environment may result in acute inhalation poisoning, depending on the level of concentration and exposure time. No toxicological data is available for the mixture.

Acute toxicity

Based on available data the classification criteria are not met.

Skin corrosion/irritation

Causes skin irritation.

Serious eye damage/irritation

Causes serious eye irritation.

Respiratory or skin sensitisation

Based on available data the classification criteria are not met.

Germ cell mutagenicity

Carcinogenicity

Based on available data the classification criteria are not met.

Reproductive toxicity

Based on available data the classification criteria are not met.

Toxicity for specific target organ - single exposure

May cause drowsiness or dizziness.

Toxicity for specific target organ - repeated exposure

Based on available data the classification criteria are not met.

Aspiration hazard

Based on available data the classification criteria are not met.

11.2. Information on other hazards

The mixture does not contain substances with endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605.

SECTION 12: Ecological information

12.1. Toxicity

Acute toxicity

12.2. Persistence and degradability

not available

12.3. Bioaccumulative potential

Not available.

12.4. Mobility in soil

Not available.

SAFETY DATA SHEET

BIODUR®

according to Commission Regulation (EU) 2020/878 as amended

BIODUR ACRYLIC PRIMER

Creation date 28th March 2023
Revision date Version 1.0

12.5. Results of PBT and vPvB assessment

Product does not contain any substance meeting the criteria for PBT or vPvB in accordance with the Annex XIII of Regulation (EC) No 1907/2006 (REACH) as amended.

12.6. Endocrine disrupting properties

The mixture does not contain substances with endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605.

12.7. Other adverse effects

Not available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Hazard of environmental contamination; dispose of the waste in accordance with the local and/or national regulations. Proceed in accordance with valid regulations on waste disposal. Any unused product and contaminated packaging should be put in labelled containers for waste collection and submitted for disposal to a person authorised for waste removal (a specialized company) that is entitled for such activity. Do not empty unused product in drainage systems. The product must not be disposed of with municipal waste. Empty containers may be used at waste incinerators to produce energy or deposited in a dump with appropriate classification. Perfectly cleaned containers can be submitted for recycling.

Waste management legislation

Directive 2008/98/EC of the European Parliament and of the Council of 19 November 2008 on waste, as amended. Decision 2000/532/EC establishing a list of wastes, as amended.

SECTION 14: Transport information

14.1. UN number or ID number

UN 1950

14.2. UN proper shipping name

AEROSOLS

14.3. Transport hazard class(es)

2 Gases

14.4. Packing group

not relevant

14.5. Environmental hazards

not relevant

14.6. Special precautions for user

Reference in the Sections 4 to 8.

14.7. Maritime transport in bulk according to IMO instruments

not relevant


Additional information

Hazard identification No.

UN number

Classification code

Safety signs



5F

2.1



SAFETY DATA SHEET

BIODUR®

according to Commission Regulation (EU) 2020/878 as amended

BIODUR ACRYLIC PRIMER

| | | | |
|---------------|-----------------|---------|-----|
| Creation date | 28th March 2023 | Version | 1.0 |
| Revision date | | | |

Road transport - ADR

| | |
|---------------------|--------------------|
| Special provisions | 190, 327, 344, 625 |
| Limited quantities | 1 L |
| Excepted quantities | E0 |

Packaging

| | |
|----------------------------|---------------|
| Packing instructions | P207, LP200 |
| Special packing provisions | PP87, RR6, L2 |
| Mixed packing provisions | MP9 |
| Transport category | 2 |
| Tunnel restriction code | (D/E) |

Special provision for

| | |
|---------------------------------|-----------|
| packages | V14 |
| loading, unloading and handling | CV9, CV12 |
| operation | S2 |

Railway transport - RID

| | |
|---------------------|--------------------|
| Special provisions | 190, 327, 344, 625 |
| Excepted quantities | E0 |

Packaging

| | |
|----------------------------|---------------|
| Packing instructions | P207, LP200 |
| Special packing provisions | PP87, RR6, L2 |
| Mixed packing provisions | MP9 |
| Transport category | 0 |

Special provision for

| | |
|---------------------------------|-------------|
| packages | W 14 |
| loading, unloading and handling | CW 9, CW 12 |

Air transport - ICAO/IATA

| | |
|---|------|
| Packaging instructions for limited amount | Y203 |
| Packaging instructions passenger | 203 |
| Cargo packaging instructions | 203 |

Marine transport - IMDG

| | |
|----------------------|----------|
| EmS (emergency plan) | F-D, S-U |
| MFAG | 620 |

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Regulation (EC) No. 1907/2006 of the European Parliament and of the Council of 18th December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing the European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No. 793/93 and Commission Regulation (EC) No. 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC, as amended. REGULATION (EC) No. 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL as amended. Commission Regulation (EU) 2020/878 of 18 June 2020 amending Annex II to Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH).

15.2. Chemical safety assessment

not available

SECTION 16: Other information

A list of standard risk phrases used in the safety data sheet

| | |
|------|---|
| H220 | Extremely flammable gas. |
| H222 | Extremely flammable aerosol. |
| H225 | Highly flammable liquid and vapour. |
| H226 | Flammable liquid and vapour. |
| H229 | Pressurised container: May burst if heated. |
| H280 | Contains gas under pressure; may explode if heated. |
| H315 | Causes skin irritation. |

SAFETY DATA SHEET

BIODUR®

according to Commission Regulation (EU) 2020/878 as amended

BIODUR ACRYLIC PRIMER

| | | | |
|---------------|-----------------|---------|-----|
| Creation date | 28th March 2023 | Version | 1.0 |
| Revision date | | | |

H319 Causes serious eye irritation.
H336 May cause drowsiness or dizziness.

Guidelines for safe handling used in the safety data sheet

P101 If medical advice is needed, have product container or label at hand.
P102 Keep out of reach of children.
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211 Do not spray on an open flame or other ignition source.
P251 Do not pierce or burn, even after use.
P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C.

A list of additional standard phrases used in the safety data sheet

EUH211 Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.
EUH066 Repeated exposure may cause skin dryness or cracking.

Other important information about human health protection

The product must not be - unless specifically approved by the manufacturer/importer - used for purposes other than as per the Section 1. The user is responsible for adherence to all related health protection regulations.

Key to abbreviations and acronyms used in the safety data sheet

ADR European agreement concerning the international carriage of dangerous goods by road
BCF Bioconcentration Factor
CAS Chemical Abstracts Service
CLP Regulation (EC) No 1272/2008 on classification, labelling and packaging of substance and mixtures
EC Identification code for each substance listed in EINECS
EINECS European Inventory of Existing Commercial Chemical Substances
EmS Emergency plan
EU European Union
EuPCS European Product Categorisation System
IATA International Air Transport Association
IBC International Code For The Construction And Equipment of Ships Carrying Dangerous Chemicals
ICAO International Civil Aviation Organization
IMDG International Maritime Dangerous Goods
IMO International Maritime Organization
INCI International Nomenclature of Cosmetic Ingredients
ISO International Organization for Standardization
IUPAC International Union of Pure and Applied Chemistry
log Kow Octanol-water partition coefficient
OEL Occupational Exposure Limits
PBT Persistent, Bioaccumulative and Toxic
ppm Parts per million
Press. Gas (Comp.) Gas under pressure: compressed gas
Press. Gas (Diss.) Gas under pressure: dissolved gas
Press. Gas (Liq.) Gas under pressure: liquefied gas
Press. Gas (Ref. Liq.) Gas under pressure: refrigerated liquefied gas
REACH Registration, Evaluation, Authorisation and Restriction of Chemicals
RID Agreement on the transport of dangerous goods by rail
UN Four-figure identification number of the substance or article taken from the UN Model Regulations
UVCB Substances of unknown or variable composition, complex reaction products or biological materials
VOC Volatile organic compounds
vPvB Very Persistent and very Bioaccumulative
Aerosol Aerosol

SAFETY DATA SHEET

BIODUR®

according to Commission Regulation (EU) 2020/878 as amended

BIODUR ACRYLIC PRIMER

| | | | |
|---------------|-----------------|---------|-----|
| Creation date | 28th March 2023 | Version | 1.0 |
| Revision date | | | |

| | |
|-------------|--|
| Eye Irrit. | Eye irritation |
| Flam. Gas | Flammable gas |
| Flam. Liq. | Flammable liquid |
| Press. Gas | Gases under pressure |
| Skin Irrit. | Skin irritation |
| STOT SE | Specific target organ toxicity - single exposure |

Training guidelines

Inform the personnel about the recommended ways of use, mandatory protective equipment, first aid and prohibited ways of handling the product.

Recommended restrictions of use

not available

Information about data sources used to compile the Safety Data Sheet

REGULATION (EC) No. 1907/2006 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL (REACH) as amended.
REGULATION (EC) No. 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL as amended. Data from the manufacturer of the substance / mixture, if available - information from registration dossiers.

More information

Classification procedure - calculation method.

Statement

The safety data sheet provides information aimed at ensuring safety and health protection at work and environmental protection. The provided information corresponds to the current status of knowledge and experience and complies with valid legal regulations. The information should not be understood as guaranteeing the suitability and usability of the product for a particular application.