

SAFETY DATA SHEET

BIODUR®

according to Commission Regulation (EU) 2020/878 as amended

BIODUR ENAMEL FLUORESCENT

Creation date	26th March 2023		
Revision date	28th January 2025	Version	3.0

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Substance / mixture

BIODUR ENAMEL FLUORESCENT

UFI

mixture

0D10-10T2-A007-EHNP

1.2. Relevant identified uses of the substance or mixture and uses advised against

Mixture's intended use

For a bright design, adverts, marking, signs etc. For painting different surfaces previously treated with white primer. Not UV resistant.

Main intended use

PC-PNT-1 Aerosol paints and coatings

Mixture uses advised against

The product should not be used in ways other than those referred in Section 1.

1.3. Details of the supplier of the safety data sheet

Importer

Name or trade name

BIODUR Sp. z o. o.

Address

Elektronowa 2E, II piętro , WARSZAWA, 03-219
Poland

Identification number (CRN)

6762484086

VAT Reg No

PL6762484086

Phone

+48 123 766552

E-mail

info@biodur.pl

Web address

www.biodur.pl

Manufacturer

Name or trade name

"NEWTON-PROMSERVICE" LLC

Address

Chichibabina str, 9, app. 110, Kharkov, 61058
Ukraine

Phone

0800-31-34-85

E-mail

e-marketing@newton.ua

Web address

newton.ua

Competent person responsible for the safety data sheet

Name

BIODUR Sp. z o. o.

E-mail

info@biodur.pl

1.4. Emergency telephone number

European emergency number: 112

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification of the mixture in accordance with Regulation (EC) No 1272/2008

The mixture is classified as dangerous.

Aerosol 1, H222, H229

Eye Irrit. 2, H319

STOT SE 3, H336

Most serious adverse physico-chemical effects

Pressurised container: May burst if heated. Extremely flammable aerosol.

Most serious adverse effects on human health and the environment

May cause drowsiness or dizziness. Causes serious eye irritation.

SAFETY DATA SHEET

BIODUR®

according to Commission Regulation (EU) 2020/878 as amended

BIODUR ENAMEL FLUORESCENT

Creation date 26th March 2023
Revision date 28th January 2025 Version 3.0

2.2. Label elements

Hazard pictogram



Signal word

Danger

Hazardous substances

methyl acetate

ethyl acetate

n-butyl acetate

Hazard statements

H222 Extremely flammable aerosol.
H229 Pressurised container: May burst if heated.
H319 Causes serious eye irritation.
H336 May cause drowsiness or dizziness.

Precautionary statements

P102 Keep out of reach of children.
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211 Do not spray on an open flame or other ignition source.
P251 Do not pierce or burn, even after use.
P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C.
P501 Dispose of contents/container to be handing over to the person authorized to dispose of waste or by returning to the supplier.

Supplemental information

EUH066 Repeated exposure may cause skin dryness or cracking.
EUH211 Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

Density 0.75-0.95 g/cm³ at 15 °C
VOC limit value cat. A (I) WB: 200 g/l

2.3. Other hazards

The mixture does not contain substances with endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605. Mixture does not contain any substance meet the criteria for PBT or vPvB in accordance with Annex XIII of Regulation (EC) No. 1907/2006 (REACH) as amended. Does not contain any PMT or vPvM components.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Mixture contains these hazardous substances and substances with the highest permissible concentration in the working environment

Identification numbers	Substance name	Content in % weight	Classification according to Regulation (EC) No 1272/2008	Note
Index: 601-003-00-5 CAS: 74-98-6 EC: 200-827-9	propane	>35	Press. Gas, Flam. Gas 1, H220	2
Index: 607-021-00-X CAS: 79-20-9 EC: 201-185-2	methyl acetate	<30	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336 EUH066	
Index: 601-004-00-0 CAS: 106-97-8 EC: 203-448-7	butane	<15	Press. Gas, Flam. Gas 1, H220	1, 2

SAFETY DATA SHEET

BIODUR®

according to Commission Regulation (EU) 2020/878 as amended

BIODUR ENAMEL FLUORESCENT

Creation date 26th March 2023
Revision date 28th January 2025 Version 3.0

Identification numbers	Substance name	Content in % weight	Classification according to Regulation (EC) No 1272/2008	Note
Index: 607-022-00-5 CAS: 141-78-6 EC: 205-500-4	ethyl acetate	<15	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336 EUH066	3
Index: 607-025-00-1 CAS: 123-86-4 EC: 204-658-1	n-butyl acetate	<10	Flam. Liq. 3, H226 STOT SE 3, H336 EUH066	3

Notes

- Note C: Some organic substances may be marketed either in a specific isomeric form or as a mixture of several isomers. In this case the supplier must state on the label whether the substance is a specific isomer or a mixture of isomers.*
- Note U (Table 3): When put on the market gases have to be classified as "Gases under pressure", in one of the groups compressed gas, liquefied gas, refrigerated liquefied gas or dissolved gas. The group depends on the physical state in which the gas is packaged and therefore has to be assigned case by case. The following codes are assigned:*

*Press. Gas (Comp.)
Press. Gas (Liq.)
Press. Gas (Ref. Liq.)
Press. Gas (Diss.)*

Aerosols shall not be classified as gases under pressure (See Annex I, Part 2, Section 2.3.2.1, Note 2).

- A substance for which exposure limits are set.*

Full text of all classifications and hazard statements is given in the section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

If any health problems are manifested or if in doubt, inform a doctor and show him information from this safety data sheet.

If inhaled

Terminate the exposure immediately; move the affected person to fresh air. Protect the person against growing cold. Provide medical treatment if irritation, dyspnoea or other symptoms persist.

If on skin

Remove contaminated clothes. Wash the affected area with plenty of water, lukewarm if possible.

If in eyes

Rinse eyes immediately with a flow of running water, open the eyelids (also using force if needed); remove contact lenses immediately if worn by the affected person. Rinsing should continue at least for 10 minutes. Provide medical treatment, specialized if possible.

If swallowed

Unlikely.

4.2. Most important symptoms and effects, both acute and delayed

If inhaled

May cause drowsiness or dizziness.

If on skin

Not expected.

If in eyes

Causes serious eye irritation.

If swallowed

Irritation, nausea.

4.3. Indication of any immediate medical attention and special treatment needed

Symptomatic treatment.

SAFETY DATA SHEET

BIODUR®

according to Commission Regulation (EU) 2020/878 as amended

BIODUR ENAMEL FLUORESCENT

Creation date 26th March 2023
Revision date 28th January 2025 Version 3.0

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Alcohol-resistant foam, carbon dioxide, powder, water spray jet, water mist.

Unsuitable extinguishing media

Water - full jet.

5.2. Special hazards arising from the substance or mixture

In the event of fire, carbon monoxide, carbon dioxide and other toxic gases may arise. Inhalation of hazardous degradation (pyrolysis) products may cause serious health damage.

5.3. Advice for firefighters

Self-Contained Breathing Apparatus (SCBA) with a chemical protection suit only where personal (close) contact is likely. Use a self-contained breathing apparatus and full-body protective clothing. Closed containers with the product near the fire should be cooled with water. Do not allow run-off of contaminated fire extinguishing material to enter drains or surface and ground water.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Provide sufficient ventilation. Pressurised container: May burst if heated. Extremely flammable aerosol. Remove all ignition sources. Use personal protective equipment for work. Follow the instructions in the Sections 7 and 8. Do not inhale aerosols. Prevent contact with skin and eyes.

6.2. Environmental precautions

Prevent contamination of the soil and entering surface or ground water.

6.3. Methods and material for containment and cleaning up

Spilled product should be covered with suitable (non-flammable) absorbing material (sand, diatomaceous earth, earth and other suitable absorption materials); to be contained in well closed containers and removed as per the Section 13. In the event of leakage of the substantial amount of the product, inform fire brigade and other competent bodies. After removal of the product, wash the contaminated site with plenty of water. Do not use solvents.

6.4. Reference to other sections

See the Section 7, 8 and 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Prevent formation of gases and vapours in flammable or explosive concentrations and concentrations exceeding the occupational exposure limits. The product should be used only in the areas where it is not in contact with open fire and other ignition sources. Use non-sparking tools. Use of antistatic clothes and footwear is recommended. Do not inhale aerosols. Prevent contact with skin and eyes. No smoking. Protect against direct sunlight. Do not pierce or burn, even after use. Wash hands and exposed parts of the body thoroughly after handling. Do not spray on an open flame or other ignition source. Use only outdoors or in a well-ventilated area. Use personal protective equipment as per Section 8. Observe valid legal regulations on safety and health protection.

7.2. Conditions for safe storage, including any incompatibilities

Store in tightly closed containers in cold, dry and well ventilated areas designated for this purpose. Store locked up. Protect from sunlight. Keep container tightly closed. Do not expose to temperatures exceeding 50 °C.

Content	Packaging type	Material of package
400 ml	aerosol can	FE

7.3. Specific end use(s)

not available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

The mixture contains substances for which occupational exposure limits are set.

European Union

Commission Directive (EU) 2017/164

Substance name (component)	Type	Value
ethyl acetate (CAS: 141-78-6)	OEL 8 hours	734 mg/m ³

SAFETY DATA SHEET

BIODUR®

according to Commission Regulation (EU) 2020/878 as amended

BIODUR ENAMEL FLUORESCENT

Creation date 26th March 2023
Revision date 28th January 2025 Version 3.0

European Union

Commission Directive (EU) 2017/164

Substance name (component)	Type	Value
ethyl acetate (CAS: 141-78-6)	OEL 8 hours	200 ppm
	OEL 15 minutes	1468 mg/m ³
	OEL 15 minutes	400 ppm

European Union

Commission Directive (EU) 2019/1831

Substance name (component)	Type	Value
n-butyl acetate (CAS: 123-86-4)	OEL 8 hours	241 mg/m ³
	OEL 8 hours	50 ppm
	OEL 15 minutes	723 mg/m ³
	OEL 15 minutes	150 ppm

8.2. Exposure controls

Follow the usual measures intended for health protection at work and especially for good ventilation. This can be achieved only by local suction or efficient general ventilation. If exposure limits cannot be observed in this mode, suitable protection of airways must be used. Do not eat, drink and smoke during work. Wash your hands thoroughly with water and soap after work and before breaks for a meal and rest.

Eye/face protection

Protective goggles.

Skin protection

Hand protection: Protective gloves resistant to the product. Contaminated skin should be washed thoroughly.

Respiratory protection

Halfmask with a filter against organic vapours or a self-contained breathing apparatus as appropriate if exposure limit values of substances are exceeded or in a poorly ventilated environment.

Thermal hazard

Not available.

Environmental exposure controls

Observe usual measures for protection of the environment, see Section 6.2.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	liquid
Colour	in accordance with the specification
Odour	characteristic
Melting point/freezing point	data not available
Boiling point or initial boiling point and boiling range	data not available
Flammability	data not available
Lower and upper explosion limit	data not available
Flash point	data not available
Auto-ignition temperature	data not available
Decomposition temperature	data not available
pH	data not available
Kinematic viscosity	data not available
Solubility in water	data not available
Partition coefficient n-octanol/water (log value)	data not available
Vapour pressure	data not available
Density and/or relative density	
Density	0.75-0.95 g/cm ³ at 15 °C
Relative vapour density	data not available
Particle characteristics	data not available

9.2. Other information

SAFETY DATA SHEET

BIODUR®

according to Commission Regulation (EU) 2020/878 as amended

BIODUR ENAMEL FLUORESCENT

Creation date	26th March 2023		
Revision date	28th January 2025	Version	3.0

VOC limit value

cat. A (I) WB: 200 g/l

SECTION 10: Stability and reactivity

10.1. Reactivity

not available

10.2. Chemical stability

The product is stable under normal conditions.

10.3. Possibility of hazardous reactions

Unknown.

10.4. Conditions to avoid

The product is stable and no degradation occurs under normal use. Protect against flames, sparks, overheating and against frost. Pressurised container: May burst if heated.

10.5. Incompatible materials

Protect against strong acids, bases and oxidizing agents.

10.6. Hazardous decomposition products

Not developed under normal uses. Dangerous outcomes such as carbon monoxide and carbon dioxide are formed at high temperature and in fire.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Inhalation of solvent vapors above values exceeding exposure limits for working environment may result in acute inhalation poisoning, depending on the level of concentration and exposure time. No toxicological data is available for the mixture.

Acute toxicity

Based on available data the classification criteria are not met.

Skin corrosion/irritation

Based on available data the classification criteria are not met.

Serious eye damage/irritation

Causes serious eye irritation.

Respiratory or skin sensitisation

Based on available data the classification criteria are not met.

Germ cell mutagenicity

not available

Carcinogenicity

Based on available data the classification criteria are not met.

Reproductive toxicity

Based on available data the classification criteria are not met.

Toxicity for specific target organ - single exposure

May cause drowsiness or dizziness.

Toxicity for specific target organ - repeated exposure

Based on available data the classification criteria are not met.

Aspiration hazard

Based on available data the classification criteria are not met.

SAFETY DATA SHEET

BIODUR®

according to Commission Regulation (EU) 2020/878 as amended

BIODUR ENAMEL FLUORESCENT

Creation date	26th March 2023		
Revision date	28th January 2025	Version	3.0

11.2. Information on other hazards

Endocrine disrupting properties

Based on the available data, the criteria for classification of the mixture are not met. Does not contain any components that may cause endocrine disruption for humans.

Other information

not available

SECTION 12: Ecological information

12.1. Toxicity

not available

12.2. Persistence and degradability

not available

12.3. Bioaccumulative potential

Not available.

12.4. Mobility in soil

Not available.

12.5. Results of PBT and vPvB assessment

Based on the available data, the criteria for classification of the mixture are not met. Does not contain any PBT or vPvB components.

12.6. Endocrine disrupting properties

Based on the available data, the criteria for classification of the mixture are not met. Does not contain any components that may cause endocrine disruption in the environment.

12.7. Other adverse effects

Not available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Hazard of environmental contamination; dispose of the waste in accordance with the local and/or national regulations. Any unused product and contaminated packaging should be put in labelled containers for waste collection and submitted for disposal to a person authorised for waste removal (a specialized company) that is entitled for such activity. Do not empty unused product in drainage systems. The product must not be disposed of with municipal waste. Empty containers may be used at waste incinerators to produce energy or deposited in a dump with appropriate classification. Perfectly cleaned containers can be submitted for recycling.

Waste management legislation

Directive 2008/98/EC of the European Parliament and of the Council of 19 November 2008 on waste, as amended. Decision 2000/532/EC establishing a list of wastes, as amended.

01 00 00 WASTES RESULTING FROM EXPLORATION, MINING, QUARRYING, AND PHYSICAL AND CHEMICAL TREATMENT OF MINERALS

SECTION 14: Transport information

14.1. UN number or ID number

UN 1950

14.2. UN proper shipping name

AEROSOLS

14.3. Transport hazard class(es)

2 Gases

14.4. Packing group

not relevant

14.5. Environmental hazards

not relevant

14.6. Special precautions for user

not available

14.7. Maritime transport in bulk according to IMO instruments

not relevant

SAFETY DATA SHEET

BIODUR®

according to Commission Regulation (EU) 2020/878 as amended

BIODUR ENAMEL FLUORESCENT

Creation date 26th March 2023
Revision date 28th January 2025 Version 3.0

Additional information

Hazard identification No.

UN number

Classification code

Safety signs



5F

Road transport - ADR


Special provisions

Limited quantities

Sign

190, 327, 344, 625

1 L



Excepted quantities

Packaging

Packing instructions

Special packing provisions

Mixed packing provisions

Transport category

Tunnel restriction code

Special provision for

packages

loading, unloading and handling

operation

E0

P207, LP200

PP87, RR6, L2

MP9

2

(D)

V14

CV9, CV12

S2

Railway transport - RID

Special provisions

Excepted quantities

Packaging

Packing instructions

Special packing provisions

Mixed packing provisions

Transport category

Special provision for

packages

loading, unloading and handling

190, 327, 344, 625

E0

P207, LP200

PP87, RR6, L2

MP9

0

W14

CW9, CW12

Air transport - ICAO/IATA

Packaging instructions for limited amount

Packaging instructions passenger

Cargo packaging instructions

Y203

203

203

Marine transport - IMDG

EmS (emergency plan)

MFAG

F-D, S-U

620

SAFETY DATA SHEET

BIODUR®

according to Commission Regulation (EU) 2020/878 as amended

BIODUR ENAMEL FLUORESCENT

Creation date	26th March 2023		
Revision date	28th January 2025	Version	3.0

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Regulation (EC) No. 1907/2006 of the European Parliament and of the Council of 18th December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing the European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No. 793/93 and Commission Regulation (EC) No. 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC, as amended. REGULATION (EC) No. 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL as amended. Commission Regulation (EU) 2020/878 of 18 June 2020 amending Annex II to Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH).

15.2. Chemical safety assessment

not available

SECTION 16: Other information

A list of standard risk phrases used in the safety data sheet

EUH066	Repeated exposure may cause skin dryness or cracking.
EUH211	Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.
H220	Extremely flammable gas.
H222	Extremely flammable aerosol.
H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H229	Pressurised container: May burst if heated.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.

Guidelines for safe handling used in the safety data sheet

P102	Keep out of reach of children.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211	Do not spray on an open flame or other ignition source.
P251	Do not pierce or burn, even after use.
P410+P412	Protect from sunlight. Do not expose to temperatures exceeding 50 °C.
P501	Dispose of contents/container to by handing over to the person authorized to dispose of waste or by returning to the supplier.

Other important information about human health protection

The product must not be - unless specifically approved by the manufacturer/importer - used for purposes other than as per the Section 1. The user is responsible for adherence to all related health protection regulations.

Key to abbreviations and acronyms used in the safety data sheet

ADR	European agreement concerning the international carriage of dangerous goods by road
Aerosol	Aerosol
BCF	Bioconcentration Factor
CAS	Chemical Abstracts Service
CLP	Regulation (EC) No 1272/2008 on classification, labelling and packaging of substance and mixtures
EC	Identification code for each substance listed in EINECS
EINECS	European Inventory of Existing Commercial Chemical Substances
EmS	Emergency plan
EU	European Union
EuPCS	European Product Categorisation System
Eye Irrit.	Eye irritation
Flam. Gas	Flammable gas
Flam. Liq.	Flammable liquid
IATA	International Air Transport Association
IBC	International Code For The Construction And Equipment of Ships Carrying Dangerous Chemicals
ICAO	International Civil Aviation Organization

SAFETY DATA SHEET

BIODUR®

according to Commission Regulation (EU) 2020/878 as amended

BIODUR ENAMEL FLUORESCENT

Creation date	26th March 2023	Version	3.0
Revision date	28th January 2025		

IMDG	International Maritime Dangerous Goods
IMO	International Maritime Organization
INCI	International Nomenclature of Cosmetic Ingredients
ISO	International Organization for Standardization
IUPAC	International Union of Pure and Applied Chemistry
log Kow	Octanol-water partition coefficient
OEL	Occupational Exposure Limits
PBT	Persistent, bioaccumulative and toxic
PMT	Persistent, mobile and toxic
ppm	Parts per million
Press. Gas (Comp.)	Gas under pressure: compressed gas
Press. Gas (Diss.)	Gas under pressure: dissolved gas
Press. Gas (Liq.)	Gas under pressure: liquefied gas
Press. Gas (Ref. Liq.)	Gas under pressure: refrigerated liquefied gas
REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals
RID	Agreement on the transport of dangerous goods by rail
STOT SE	Specific target organ toxicity - single exposure
UN	Four-figure identification number of the substance or article taken from the UN Model Regulations
UVCB	Substances of unknown or variable composition, complex reaction products or biological materials
VOC	Volatile organic compounds
vPvB	Very persistent and very bioaccumulative
vPvM	Very persistent and very mobile

Training guidelines

Inform the personnel about the recommended ways of use, mandatory protective equipment, first aid and prohibited ways of handling the product.

Recommended restrictions of use

not available

Information about data sources used to compile the Safety Data Sheet

REGULATION (EC) No. 1907/2006 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL (REACH) as amended.
REGULATION (EC) No. 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL as amended. Data from the manufacturer of the substance / mixture, if available - information from registration dossiers.

The changes (which information has been added, deleted or modified)

The version 3.0 replaces the SDS version from Sunday, 26 March 2023. Changes were made in sections 1, 2, 11, 12, 13 and 16.

More information

Classification procedure - calculation method.

Statement

The safety data sheet provides information aimed at ensuring safety and health protection at work and environmental protection. The provided information corresponds to the current status of knowledge and experience and complies with valid legal regulations. The information should not be understood as guaranteeing the suitability and usability of the product for a particular application.