

Technical Information

Dependable corrosion protection, ideal base for automotive paint coating. Forms a strong, quick-drying protective layer, ready for sanding 30 min after application. Provides splendid corrosion protection. It has excellent filling capacity: the resulting layer of primer fills the scratches and dents that formed during the processing of the previous layers.

A high percentage of dry residue of auto primer can significantly reduce the consumption of auto enamel. The primed surface is resistant to mechanical impacts and weathering. Highly durable.

Used for painting preparation or restoration of paint coat of cars, motorcycles, motor scooters, bicycles, snowmobiles, agricultural machinery, small boats, water scooters and speed boats. For exterior and interior use.

Quality & properties

Effective protection
against rust

Provides high
adhesion

Dries quickly

Physical & chemical data

Content: 500 ml

Base: acryl resin

Color : according to the assortment

Paint effect : matt

Coverage area: 2,3-3,0 m²

Drying time to degree 3 at 20 (±2)°C: no
more 30 minutes

Density at 20 (±2)°C: 0,75-1,20 g/cm³

Coating adhesion to metal : no more 2 score

How to use

Before use, carefully read the directions on the packaging and act accordingly.

The surface should be clean, dry and free of grease. Remove loose old lacquer and rust and sand the surface.

The aerosol should have room temperature. Best processing temperature 15 to 30°C.

Before use, shake the aerosol for 2 minutes and spray a sample. Distance to the surface to be treated approximately 25 to 30 centimetre.

Apply the primer in several thin layers. Before applying the next layer, again shake the aerosol.

After use, clean the valve (turn aerosol upside down and press the nozzle for approximately 5 seconds).

The drying time depends on the ambient temperature, the humidity of the air and the thickness of the lacquer applied.

Conditions of storage and transportation of products: Products are transported by any ground mode of transport in compliance with the rules of cargo transportation. Products in packaged form must be stored in premises that protect products from chemical influences and mechanical damage at a temperature not lower than minus 20C and not higher than plus 40C.

Stability during storage: 5 years from the date of manufacture. The date of manufacture is indicated on the bottom of the aerosol.

Regulatory and legislative information

Regulation (EC) No. 1907/2006 of the European Parliament and of the Council of 18th December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing the European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No. 793/93 and Commission Regulation (EC) No. 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC, as amended. REGULATION (EC) No.

1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL as amended. Commission Regulation (EU) 2020/878 of 18 June 2020 amending Annex II to Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH).

