

BIODUR®

BIODUR Sp. z o. o.

Krakow, Halicka str. 9, 31-036, Poland
Tel: +4812 376 6552
info@biodur.pl
www.biodur.pl

TECHNICAL DATA SHEET

ACRYLIC LACQUER

Product description

Fast-drying acrylic clearcoat applied to both cleaned and painted surfaces: metal, wood, glass, stone, brick and some plastics. It creates a gloss effect, results in a stronger saturation of colors. Apply to the surface for 30 minutes. Resistant to mechanical and atmospheric factors. Does not fade out.

Product characteristics

Fast drying
Excellent filling property
Long-lasting gloss
Scratch free and shockproof
Resistant to weather exposure
Corrosion preventive
UV-resistant and non-fading
Excellent adhesion

Physical and Chemical Characteristics

Contents	500 ml
Base	Acrylic resin
Gloss	High gloss
Coverage	1,25 to 1,75 m ²
Dust dry	After 10 to 30 minutes
Tack free	After 3 to 4 hours
Hardened/re-sprayable	After 24 hours
Heat resistant	To 110°C

Usage

Before use, carefully read the instructions on the packaging and act accordingly.

Pre Treatment

Clean, dry and degrease the surface.

Treatment

The surface should be clean, dry and free of grease. The aerosol should have temperature between +15 to +30°C. Best processing temperature +15 to +25°C. Before use, shake the aerosol for 2 minutes and make a test spray. Keep the distance to the surface that has to be treated approximately 25 to 30 centimetre.

Apply the lacquer in several thin layers. Before applying the next layer, again shake the aerosol.

After use, clean the valve (turn aerosol upside down and press the actuator till you see clear spray).

The drying time depends on the ambient temperature, the humidity of the air and thickness of applied coating.