

# BIODUR®

---

## BIODUR Sp. z o. o.

Krakow, Halicka str. 9, 31-036, Poland  
Tel: +4812 376 6552  
info@biodur.pl  
www.biodur.pl

## TECHNICAL DATA SHEET

### FOREST MARKING SPRAY

#### Product description

Special fluorescent paint for marking in the forest, making inscriptions, numbering of trees, soil, stones. The special self-cleaning valve "360" allows applying the paint both vertically and horizontally as well as used at any angle convenient for use. The ergonomic dispenser allows you to create precise and clear inscriptions, keep your hands clean at work. High visibility, excellent adhesion on various substrates, also on wet surfaces. Thanks to the high content of pigments, the paint has excellent reflective properties resistant to UV agents and atmospheric factors.

#### Product characteristics

- Fast drying
- High coverage
- Resistant to weather exposure
- Excellent adhesion
- Bright colours
- Directed spray for signs application
- Ergonomic cap for better protection

#### Physical and Chemical Characteristics

Contents	400 ml
Base	Acrylic resin
Gloss	Matt
Coverage	1,25 to 1,75 m <sup>2</sup>
Dust dry	After 10 to 30 minutes
Tack free	After 3 to 4 hours
Hardened/re-sprayable	After 24 hours
Heat resistant	To 110°C

**Before use, carefully read the instructions on the packaging and act accordingly.**

#### Treatment

Best processing temperature -10 to +45°C. Before use, shake the aerosol for 2 minutes and make a test spray.