

# SAFETY DATA SHEET

according to Regulation (EC) No 1907/2006 (REACH) as amended

## BIODUR Enamel "super chrome"

Creation date 16th November 2022  
Revision date Version 1.0

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

**1.1. Product identifier** BIODUR Enamel "super chrome"  
Substance / mixture mixture  
UFI 7410-H0QV-D00R-EGWG

**1.2. Relevant identified uses of the substance or mixture and uses advised against**  
**Mixture's intended use**

Quickly drying enamel based on synthetic acrylic resins. Forms decorative glossy finish with a metallic sheen. Thanks to "mirror" effect chroming has a high reflectivity property. For internal work.

Suitable for restoration and decorative painting smooth surfaces of articles made of metal, wood, glass, ceramics, some sort of plastic. Indispensable for painting works of art and decorative elements: art frames, emblems, cups, pieces of chandeliers, figurines, candlesticks, and icons.

**Main intended use**

PC-PNT-1 Aerosol paints and coatings

**Mixture uses advised against**

The product should not be used in ways other than those referred in Section 1.

**1.3. Details of the supplier of the safety data sheet**

**Importer**

Name or trade name **BIODUR Sp. z o. o.**  
Address ul. Modlińska 6a, lok. 224 , Warszawa  
Poland  
VAT Reg No PL6762484086  
Phone +48123766552

**Manufacturer**

Name or trade name **"NEWTON-PROMSERVICE" LLC**  
Address App. 110 Chichibabina., 9, app. 110,  
Kharkiv Ukraine  
Phone 38-0577661720

**Competent person responsible for the safety data sheet**

Name Trial ltd.  
E-mail sblcore@sblcore.com

**1.4. Emergency telephone number**

European emergency number: 112

### SECTION 2: Hazards identification

**2.1. Classification of the substance or mixture**

**Classification of the mixture in accordance with Regulation (EC) No 1272/2008**

The mixture is classified as dangerous.

Aerosol 1, H222, H229  
Asp. Tox. 1, H304  
Skin Irrit. 2, H315  
STOT SE 3, H336  
Repr. 2, H361f  
STOT RE 2, H373  
Aquatic Chronic 2, H411

Full text of all classifications and hazard statements is given in the section 16.

**Most serious adverse physico-chemical effects**

Extremely flammable aerosol. Pressurised container: May burst if heated.

**Most serious adverse effects on human health and the environment**

Causes skin irritation. May cause damage to organs through prolonged or repeated exposure. Suspected of damaging fertility. May cause drowsiness or dizziness. May be fatal if swallowed and enters airways. Toxic to aquatic life with long lasting effects.

# SAFETY DATA SHEET

according to Regulation (EC) No 1907/2006 (REACH) as amended

## BIODUR Enamel "super chrome"

Creation date 16th November 2022  
Revision date Version 1.0

### 2.2. Label elements

#### Hazard pictogram



#### Signal word

Danger

#### Hazardous substances

xylene  
n-hexane

#### Hazard statements

H222 Extremely flammable aerosol.  
H229 Pressurised container: May burst if heated.  
H315 Causes skin irritation.  
H336 May cause drowsiness or dizziness.  
H361f Suspected of damaging fertility.  
H373 May cause damage to organs through prolonged or repeated exposure.  
H411 Toxic to aquatic life with long lasting effects.

#### Precautionary statements

P101 If medical advice is needed, have product container or label at hand.  
P102 Keep out of reach of children.  
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P211 Do not spray on an open flame or other ignition source.  
P251 Do not pierce or burn, even after use.  
P280 Wear protective gloves.  
P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C.  
P501 Dispose of contents/container to be handed over to the person authorized to dispose of waste or by returning to the supplier.

#### Supplemental information

EUH066 Repeated exposure may cause skin dryness or cracking.  
Density 0,75-0,95 g/cm<sup>3</sup> at 15 °C  
VOC limit value cat. A (I) SB: 200 g/l

#### Requirements for child-resistant fastenings and tactile warning of danger

Container must carry a tactile warning of danger.

### 2.3. Other hazards

The mixture does not contain substances with endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605. Mixture does not contain any substance meet the criteria for PBT or vPvB in accordance with Annex XIII of Regulation (EC) No. 1907/2006 (REACH) as amended.

## SECTION 3: Composition/information on ingredients

### 3.2. Mixtures

Mixture contains these hazardous substances and substances with the highest permissible concentration in the working environment

Identification numbers	Substance name	Content in % weight	Classification according to Regulation (EC) No 1272/2008	Note
Index: 601-003-00-5 CAS: 74-98-6 EC: 200-827-9	propane	≤35,0	Press. Gas, Flam. Gas 1, H220	3

# SAFETY DATA SHEET

according to Regulation (EC) No 1907/2006 (REACH) as amended

## BIODUR Enamel "super chrome"

Creation date 16th November 2022  
Revision date Version 1.0

Identification numbers	Substance name	Content in % weight	Classification according to Regulation (EC) No 1272/2008	Note
Index: 601-022-00-9 CAS: 1330-20-7 EC: 215-535-7	xylene	≤26,0	Flam. Liq. 3, H226 Acute Tox. 4, H312+H332 Skin Irrit. 2, H315	1, 4
Index: 601-037-00-0 CAS: 110-54-3 EC: 203-777-6	n-hexane	<23	Flam. Liq. 2, H225 Asp. Tox. 1, H304 Skin Irrit. 2, H315 STOT SE 3, H336 Repr. 2, H361f STOT RE 2, H373 Aquatic Chronic 2, H411 Specific concentration limit: STOT RE 2, H373: C ≥ 5 %	4
Index: 601-004-00-0 CAS: 106-97-8 EC: 203-448-7	butane	≤15,0	Press. Gas, Flam. Gas 1, H220	1, 3
Index: 013-001-00-6 CAS: 7429-90-5 EC: 231-072-3	aluminium powder (pyrophoric)	<7	Pyr. Sol. 1, H250 Water-react. 2, H261	2
Index: 030-001-01-9 CAS: 7440-66-6 EC: 231-175-3	zinc powder - zinc dust (stabilised)	<7	Aquatic Acute 1, H400 (M=1) Aquatic Chronic 1, H410 (M=1)	

### Notes

- Note C: Some organic substances may be marketed either in a specific isomeric form or as a mixture of several isomers. In this case the supplier must state on the label whether the substance is a specific isomer or a mixture of isomers.
- Note T: This substance may be marketed in a form which does not have the physical hazards as indicated by the classification in the entry in Part 3. If the results of the relevant method or methods in accordance with Part 2 of Annex I of this Regulation show that the specific form of substance marketed does not exhibit this physical property or these physical hazards, the substance shall be classified in accordance with the result or results of this test or these tests. Relevant information, including reference to the relevant test method(s) shall be included in the safety data sheet.
- Note U (Table 3): When put on the market gases have to be classified as "Gases under pressure", in one of the groups compressed gas, liquefied gas, refrigerated liquefied gas or dissolved gas. The group depends on the physical state in which the gas is packaged and therefore has to be assigned case by case. The following codes are assigned:

Press. Gas (Comp.)  
Press. Gas (Liq.)  
Press. Gas (Ref. Liq.)  
Press. Gas (Diss.)

Aerosols shall not be classified as gases under pressure (See Annex I, Part 2, Section 2.3.2.1, Note 2).

- A substance for which exposure limits are set.

Full text of all classifications and hazard statements is given in the section 16.

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

Do not perform artificial respiration without self-protection (e.g. a mask). If any health problems are manifested or if in doubt, inform a doctor and show him information from this safety data sheet.

#### If inhaled

Take care of your own safety, do not let the affected person walk! Terminate the exposure immediately; move the affected person to fresh air. Beware of the contaminated clothes. Depending on the situation, call the medical rescue service and ensure medical treatment considering the frequent need of further observation for at least 24 hours.

#### If on skin

Remove contaminated clothes. Wash the affected area with plenty of water, lukewarm if possible.

# SAFETY DATA SHEET

according to Regulation (EC) No 1907/2006 (REACH) as amended

## BIODUR Enamel "super chrome"

Creation date

16th November 2022

Revision date

Version

1.0

### **If in eyes**

Rinse eyes immediately with a flow of running water, open the eyelids (also using force if needed); remove contact lenses immediately if worn by the affected person. Rinsing should continue at least for 10 minutes. Provide medical treatment, specialized if possible.

### **If swallowed**

If the affected person vomits, make sure to prevent inhalation of the vomit (as there is a danger of lung damage after inhalation of these liquids in the airways also in infinitesimal amount). Ensure medical treatment considering the frequent need of further observation for at least 24 hours. Bring an original container with the label and the Safety Data Sheet of the given substance as appropriate.

## **4.2. Most important symptoms and effects, both acute and delayed**

### **If inhaled**

Cough, headache. May cause drowsiness or dizziness.

### **If on skin**

Causes skin irritation.

### **If in eyes**

When intruding eyes, it can evoke irritation.

### **If swallowed**

Irritation, nausea.

## **4.3. Indication of any immediate medical attention and special treatment needed**

Symptomatic treatment.

## **SECTION 5: Firefighting measures**

### **5.1. Extinguishing media**

#### **Suitable extinguishing media**

Alcohol-resistant foam, carbon dioxide, powder, water spray jet, water mist.

#### **Unsuitable extinguishing media**

Water - full jet.

### **5.2. Special hazards arising from the substance or mixture**

In the event of fire, carbon monoxide, carbon dioxide and other toxic gases may arise. Inhalation of hazardous degradation (pyrolysis) products may cause serious health damage.

### **5.3. Advice for firefighters**

Self-Contained Breathing Apparatus (SCBA) with a chemical protection suit only where personal (close) contact is likely. Use a self-contained breathing apparatus and full-body protective clothing. Closed containers with the product near the fire should be cooled with water. Do not allow run-off of contaminated fire extinguishing material to enter drains or surface and ground water.

## **SECTION 6: Accidental release measures**

### **6.1. Personal precautions, protective equipment and emergency procedures**

Provide sufficient ventilation. Extremely flammable aerosol. Pressurised container: May burst if heated. Remove all ignition sources. Use personal protective equipment for work. Follow the instructions in the Sections 7 and 8. Do not inhale aerosols. Prevent contact with skin and eyes.

### **6.2. Environmental precautions**

Do not allow to enter drains. Prevent contamination of the soil and entering surface or ground water.

### **6.3. Methods and material for containment and cleaning up**

Spilled product should be covered with suitable (non-flammable) absorbing material (sand, diatomaceous earth, earth and other suitable absorption materials); to be contained in well closed containers and removed as per the Section 13. In the event of leakage of the substantial amount of the product, inform fire brigade and other competent bodies. After removal of the product, wash the contaminated site with plenty of water. Do not use solvents.

### **6.4. Reference to other sections**

See the Section 7, 8 and 13.

# SAFETY DATA SHEET

according to Regulation (EC) No 1907/2006 (REACH) as amended

## BIODUR Enamel "super chrome"

Creation date 16th November 2022  
Revision date Version 1.0

### SECTION 7: Handling and storage

#### 7.1. Precautions for safe handling

Prevent formation of gases and vapours in flammable or explosive concentrations and concentrations exceeding the occupational exposure limits. The product should be used only in the areas where it is not in contact with open fire and other ignition sources. Use non-sparking tools. Use of antistatic clothes and footwear is recommended. Do not inhale aerosols. Prevent contact with skin and eyes. No smoking. Protect against direct sunlight. Obtain special instructions before use. Do not pierce or burn, even after use. Wash hands and exposed parts of the body thoroughly after handling. Do not handle until all safety precautions have been read and understood. Use only outdoors or in a well-ventilated area. Use personal protective equipment as per Section 8. Observe valid legal regulations on safety and health protection. Avoid release to the environment.

#### 7.2. Conditions for safe storage, including any incompatibilities

Store in tightly closed containers in cold, dry and well ventilated areas designated for this purpose. Store locked up. Protect from sunlight. Keep container tightly closed. Do not expose to temperatures exceeding 50 °C.

Content	Packaging type	Material of package
400 ml	aerosol can	FE

#### 7.3. Specific end use(s)

not available

### SECTION 8: Exposure controls/personal protection

#### 8.1. Control parameters

The mixture contains substances for which occupational exposure limits are set.

##### European Union

##### Commission Directive 2000/39/EC

Substance name (component)	Type	Value	Note
xylene (CAS: 1330-20-7)	OEL 8 hours	221 mg/m <sup>3</sup>	Skin
	OEL 8 hours	50 ppm	
	OEL 15 minutes	442 mg/m <sup>3</sup>	
	OEL 15 minutes	100 ppm	

##### European Union

##### Commission Directive 2006/15/EC

Substance name (component)	Type	Value	Note
n-hexane (CAS: 110-54-3)	OEL 8 hours	72 mg/m <sup>3</sup>	
	OEL 8 hours	20 ppm	

#### 8.2. Exposure controls

Follow the usual measures intended for health protection at work and especially for good ventilation. This can be achieved only by local suction or efficient general ventilation. If exposure limits cannot be observed in this mode, suitable protection of airways must be used. Do not eat, drink and smoke during work. Wash your hands thoroughly with water and soap after work and before breaks for a meal and rest.

##### Eye/face protection

Protective goggles.

##### Skin protection

Hand protection: Protective gloves resistant to the product. When choosing appropriate thickness, material and permeability of the gloves, observe recommendations of their particular manufacturer. Observe other recommendations of the manufacturer. Other protection: protective workwear. Contaminated skin should be washed thoroughly.

##### Respiratory protection

Respirator.

##### Thermal hazard

Data not available.

##### Environmental exposure controls

Observe usual measures for protection of the environment, see Section 6.2. Collect spillage.

# SAFETY DATA SHEET

according to Regulation (EC) No 1907/2006 (REACH) as amended

## BIODUR Enamel "super chrome"

Creation date 16th November 2022  
Revision date Version 1.0

### SECTION 9: Physical and chemical properties

#### 9.1. Information on basic physical and chemical properties

Physical state	gas
Colour	chromowanego złota, chromowanego srebra
Odour	characteristic
Melting point/freezing point	data not available
Boiling point or initial boiling point and boiling range	data not available
Flammability	data not available
Lower and upper explosion limit	data not available
Flash point	data not available
Auto-ignition temperature	data not available
Decomposition temperature	data not available
pH	gas
Kinematic viscosity	data not available
Solubility in water	data not available
Partition coefficient n-octanol/water (log value)	data not available
Vapour pressure	data not available
Density and/or relative density	
Density	0,75-0,95 g/cm <sup>3</sup> at 15 °C
Relative vapour density	data not available
Particle characteristics	data not available

#### 9.2. Other information

VOC limit value cat. A (I) SB: 200 g/l

### SECTION 10: Stability and reactivity

#### 10.1. Reactivity

not available

#### 10.2. Chemical stability

The product is stable under normal conditions.

#### 10.3. Possibility of hazardous reactions

Unknown.

#### 10.4. Conditions to avoid

The product is stable and no degradation occurs under normal use. Protect against flames, sparks, overheating and against frost. Pressurised container: May burst if heated.

#### 10.5. Incompatible materials

Protect against strong acids, bases and oxidizing agents.

#### 10.6. Hazardous decomposition products

Not developed under normal uses. Dangerous outcomes such as carbon monoxide and carbon dioxide are formed at high temperature and in fire.

### SECTION 11: Toxicological information

#### 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Inhalation of solvent vapors above values exceeding exposure limits for working environment may result in acute inhalation poisoning, depending on the level of concentration and exposure time. No toxicological data is available for the mixture.

##### Acute toxicity

Based on available data the classification criteria are not met.

##### Skin corrosion/irritation

Causes skin irritation.

##### Serious eye damage/irritation

Based on available data the classification criteria are not met.

##### Respiratory or skin sensitisation

Based on available data the classification criteria are not met.

# SAFETY DATA SHEET

according to Regulation (EC) No 1907/2006 (REACH) as amended

## BIODUR Enamel "super chrome"

Creation date	16th November 2022	Version	1.0
Revision date			

### **Germ cell mutagenicity**

Based on available data the classification criteria are not met.

### **Carcinogenicity**

Based on available data the classification criteria are not met.

### **Reproductive toxicity**

Suspected of damaging fertility.

### **Toxicity for specific target organ - single exposure**

May cause drowsiness or dizziness.

### **Toxicity for specific target organ - repeated exposure**

May cause damage to organs through prolonged or repeated exposure.

### **Aspiration hazard**

May be fatal if swallowed and enters airways.

### **11.2. Information on other hazards**

The mixture does not contain substances with endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605.

## **SECTION 12: Ecological information**

### **12.1. Toxicity**

#### **Acute toxicity**

Toxic to aquatic life with long lasting effects.

### **12.2. Persistence and degradability**

not available

### **12.3. Bioaccumulative potential**

Data not available.

### **12.4. Mobility in soil**

Data not available.

### **12.5. Results of PBT and vPvB assessment**

Product does not contain any substance meeting the criteria for PBT or vPvB in accordance with the Annex XIII of Regulation (EC) No 1907/2006 (REACH) as amended.

### **12.6. Endocrine disrupting properties**

The mixture does not contain substances with endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605.

### **12.7. Other adverse effects**

Data not available.

## **SECTION 13: Disposal considerations**

### **13.1. Waste treatment methods**

Hazard of environmental contamination; dispose of the waste in accordance with the local and/or national regulations. Proceed in accordance with valid regulations on waste disposal. Any unused product and contaminated packaging should be put in labelled containers for waste collection and submitted for disposal to a person authorised for waste removal (a specialized company) that is entitled for such activity. Do not empty unused product in drainage systems. The product must not be disposed of with municipal waste. Empty containers may be used at waste incinerators to produce energy or deposited in a dump with appropriate classification. Perfectly cleaned containers can be submitted for recycling.

#### **Waste management legislation**

Directive 2008/98/EC of the European Parliament and of the Council of 19 November 2008 on waste, as amended. Decision 2000/532/EC establishing a list of wastes, as amended.

#### **Waste type code**

01 00 00 WASTES RESULTING FROM EXPLORATION, MINING, QUARRYING, AND PHYSICAL AND CHEMICAL TREATMENT OF MINERALS

## **SECTION 14: Transport information**

### **14.1. UN number or ID number**

UN 1950

# SAFETY DATA SHEET

according to Regulation (EC) No 1907/2006 (REACH) as amended

## BIODUR Enamel "super chrome"

Creation date 16th November 2022  
Revision date Version 1.0

### 14.2. UN proper shipping name

AEROSOLS

### 14.3. Transport hazard class(es)

2 Gases

### 14.4. Packing group

not relevant

### 14.5. Environmental hazards

not relevant

### 14.6. Special precautions for user

Reference in the Sections 4 to 8.

### 14.7. Maritime transport in bulk according to IMO instruments

not relevant

#### Additional information

Hazard identification No.



UN number

1.1L

Classification code

2.1+dangerous for the environment

Safety signs



#### Road transport - ADR

Special provisions

190, 327, 344, 625

Limited quantities

1 L

Excepted quantities

E0

#### Packaging

Packing instructions

P207, LP200

Special packing provisions

PP87, RR6, L2

Mixed packing provisions

MP9

Transport category

2

Tunnel restriction code

(D)

#### Special provision for

packages

V14

loading, unloading and handling

CV9, CV12

operation

S2

#### Railway transport - RID

Special provisions

190, 327, 344, 625

Excepted quantities

E0

#### Packaging

Packing instructions

P207, LP200

Special packing provisions

PP87, RR6, L2

Mixed packing provisions

MP9

Transport category

0

#### Special provision for

packages

W 14

loading, unloading and handling

CW 9, CW 12



# SAFETY DATA SHEET

according to Regulation (EC) No 1907/2006 (REACH) as amended

## BIODUR Enamel "super chrome"

Creation date 16th November 2022  
Revision date Version 1.0

### Air transport - ICAO/IATA

Packaging instructions for limited amount Y203  
Packaging instructions passenger 203  
Cargo packaging instructions 203

### Marine transport - IMDG

EmS (emergency plan) F-D, S-U  
MFAG 620

## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Regulation (EC) No. 1907/2006 of the European Parliament and of the Council of 18th December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing the European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No. 793/93 and Commission Regulation (EC) No. 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC, as amended. REGULATION (EC) No. 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL as amended.

### 15.2. Chemical safety assessment

not available

## SECTION 16: Other information

### A list of standard risk phrases used in the safety data sheet

H220 Extremely flammable gas.  
H222 Extremely flammable aerosol.  
H225 Highly flammable liquid and vapour.  
H226 Flammable liquid and vapour.  
H229 Pressurised container: May burst if heated.  
H250 Catches fire spontaneously if exposed to air.  
H261 In contact with water releases flammable gases.

H304 May be fatal if swallowed and enters airways.  
H315 Causes skin irritation.  
H336 May cause drowsiness or dizziness.  
H361f Suspected of damaging fertility.  
H373 May cause damage to organs through prolonged or repeated exposure.  
H400 Very toxic to aquatic life.  
H410 Very toxic to aquatic life with long lasting effects.  
H411 Toxic to aquatic life with long lasting effects.  
H312+H332 Harmful in contact with skin or if inhaled.

### Guidelines for safe handling used in the safety data sheet

P101 If medical advice is needed, have product container or label at hand.  
P102 Keep out of reach of children.  
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P211 Do not spray on an open flame or other ignition source.  
P251 Do not pierce or burn, even after use.  
P280 Wear protective gloves.  
P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C.  
P501 Dispose of contents/container to by handing over to the person authorized to dispose of waste or by returning to the supplier.

### A list of additional standard phrases used in the safety data sheet

EUH066 Repeated exposure may cause skin dryness or cracking.

### Other important information about human health protection

The product must not be - unless specifically approved by the manufacturer/importer - used for purposes other than as per the Section 1. The user is responsible for adherence to all related health protection regulations.

# SAFETY DATA SHEET

according to Regulation (EC) No 1907/2006 (REACH) as amended

## BIODUR Enamel "super chrome"

Creation date 16th November 2022  
Revision date Version 1.0

### Key to abbreviations and acronyms used in the safety data sheet

ADR	European agreement concerning the international carriage of dangerous goods by road
BCF	Bioconcentration Factor
CAS	Chemical Abstracts Service
CLP	Regulation (EC) No 1272/2008 on classification, labelling and packaging of substance and mixtures
EINECS	European Inventory of Existing Commercial Chemical Substances
EmS	Emergency plan
EU	European Union
EuPCS	European Product Categorisation System
IATA	International Air Transport Association
IBC	International Code For The Construction And Equipment of Ships Carrying Dangerous Chemicals
ICAO	International Civil Aviation Organization
IMDG	International Maritime Dangerous Goods
INCI	International Nomenclature of Cosmetic Ingredients
ISO	International Organization for Standardization
IUPAC	International Union of Pure and Applied Chemistry
log Kow	Octanol-water partition coefficient
MARPOL	International Convention for the Prevention of Pollution from Ships
OEL	Occupational Exposure Limits
PBT	Persistent, Bioaccumulative and Toxic
ppm	Parts per million
Press. Gas (Comp.)	Gas under pressure: compressed gas
Press. Gas (Diss.)	Gas under pressure: dissolved gas
Press. Gas (Liq.)	Gas under pressure: liquefied gas
Press. Gas (Ref. Liq.)	Gas under pressure: refrigerated liquefied gas
REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals
RID	Agreement on the transport of dangerous goods by rail
UN	Four-figure identification number of the substance or article taken from the UN Model Regulations
UVCB	Substances of unknown or variable composition, complex reaction products or biological materials
vPvB	Very Persistent and very Bioaccumulative
EC	Identification code for each substance listed in EINECS
LOC	Volatile organic compounds
Acute Tox.	Acute toxicity
Aerosol	Aerosol
Aquatic Acute	Hazardous to the aquatic environment
Aquatic Chronic	Hazardous to the aquatic environment (chronic)
Asp. Tox.	Aspiration hazard
Flam. Gas	Flammable gas
Flam. Liq.	Flammable liquid
Press. Gas	Gases under pressure
Pyr. Sol.	Pyrophoric solid
Repr.	Reproductive toxicity
Skin Irrit.	Skin irritation
STOT RE	Specific target organ toxicity - repeated exposure
STOT SE	Specific target organ toxicity - single exposure
Water-react.	Substance or mixture which in contact with water emits flammable gas

### Training guidelines

Inform the personnel about the recommended ways of use, mandatory protective equipment, first aid and prohibited ways of handling the product.

### Recommended restrictions of use

# SAFETY DATA SHEET

according to Regulation (EC) No 1907/2006 (REACH) as amended

## BIODUR Enamel "super chrome"

Creation date	16th November 2022	Version	1.0
Revision date			

not available

### Information about data sources used to compile the Safety Data Sheet

REGULATION (EC) No. 1907/2006 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL (REACH) as amended.  
REGULATION (EC) No. 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL as amended. Data from the manufacturer of the substance / mixture, if available - information from registration dossiers.

### More information

Classification procedure - calculation method.

### Statement

The safety data sheet provides information aimed at ensuring safety and health protection at work and environmental protection. The provided information corresponds to the current status of knowledge and experience and complies with valid legal regulations. The information should not be understood as guaranteeing the suitability and usability of the product for a particular application.