

# BIODUR®

---

## BIODUR Sp. z o. o.

Krakow, Halicka str. 9, 31-036, Poland  
Tel: +4812 376 6552  
info@biodur.pl  
www.biodur.pl

## TECHNICAL DATA SHEET

## PAINT SPRAY UNIVERSAL

### Product description

Fast-drying alkyd enamel for painting metal, wood, concrete, gypsum, ceramics, glass and some types of plastic. Widely used in the automotive and industrial segments, gardening, art and decorative, hobbies and professional work at home.

### Product characteristics

Excellent coverage and filling property  
Long-lasting colour and gloss  
Scratch free and shockproof  
Resistant to chemicals and weather exposure  
Anti-corrosion  
Excellent adhesion

### Physical and Chemical Characteristics

Contents	400 ml
Base	Alkyd resin
Gloss	High gloss, matt
Coverage	1,25 to 1,75 m <sup>2</sup>
Dust dry	After 10 to 30 minutes
Tack free	After 3 to 4 hours
Hardened/re-sprayable	After 24 hours
Heat resistant	To 110°C

### Usage

**Before use, carefully read the instructions on the packaging and act accordingly.**

#### Pre Treatment

Remove loose old paint and rust and sand the surface. Clean, dry and degrease the surface.

#### Treatment

The surface should be clean, dry and free of grease. The aerosol should have temperature between +15 to +30°C. Best processing temperature +15 to +25°C. Before use, shake the aerosol for 2 minutes and make a test spray. Keep the distance to the surface that has to be treated approximately 25 to 30 centimetre.

Apply the lacquer in several thin layers. Before applying the next layer, again shake the aerosol.

After use, clean the valve (turn aerosol upside down and press the actuator till you see clear spray).

**The drying time depends on the ambient temperature, the humidity of the air and thickness of applied coating.**