	SAFE	ETY DATA SHEET BIODUR		
	according to Commiss	sion Regulation (EU) 2020/878 as amended		
	BIODUR CONS	TRUCTION MARKING SPRAY		
	on date 23rd March 2023			
Revisi	on date	Version 1.0		
SECT	ION 1: Identification of the substance/mi	xture and of the company/undertaking		
1.1.	Product identifier	BIODUR CONSTRUCTION MARKING SPRAY		
	Substance / mixture	mixture		
	UFI	5V00-00NP-G008-FG59		
1.2.	Relevant identified uses of the substand Mixture's intended use	ce or mixture and uses advised against		
	mining, industry and archeology. Provides fa	instruction, public works, topographic markings, geological studies, ast and accurate marking on asphalt, concrete, brick, clay, grass, stone, or light. Resistant to the weather impact. Excellent adhesion on wet		
	Main intended use			
	PC-PNT-1 Aerosol pair	nts and coatings		
	Mixture uses advised against			
The product should not be used in ways other than those referred in Section 1.				
L.3.	Details of the supplier of the safety data	a sheet		
	Importer			
	Name or trade name	BIODUR Sp. z o. o.		
	Address	ul. Modlińska 6a, lok. 224 , Warszawa, 03-216		
		Poland		
	Identification number (CRN)	6762484086		
	VAT Reg No	PL6762484086		
	Phone	+48123766552		
	E-mail	info@biodur.pl		
	Web address	www.biodur.pl		
	Manufacturer			
	Name or trade name	"NEWTON-PROMSERVICE" LLC		
	Address	App. 110 Chichibabina., 9, app. 110, , Charkiw Ukraine		
	Phone	0800-31-34-85		
	E-mail	e-marketing@newton.ua		
	Web address	newton.ua		
	Competent person responsible for the s	afety data sheet		
	Name	BIODUR Sp. z o. o.		
	E-mail	info@biodur.pl		
1.4.	Emergency telephone number			
	European emergency number: 112			

### 2.1. Classification of the substance or mixture


Classification of the mixture in accordance with Regulation (EC) No 1272/2008 The mixture is classified as dangerous.

Aerosol 1, H229, H222 Eye Irrit. 2, H319 STOT SE 3, H336

Full text of all classifications and hazard statements is given in the section 16.

#### Most serious adverse physico-chemical effects

Pressurised container: May burst if heated. Extremely flammable aerosol. **Most serious adverse effects on human health and the environment** Causes serious eye irritation. May cause drowsiness or dizziness.



#### 2.3. Other hazards

The mixture does not contain substances with endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605. Mixture does not contain any substance meet the criteria for PBT or vPvB in accordance with Annex XIII of Regulation (EC) No. 1907/2006 (REACH) as amended.

#### **SECTION 3: Composition/information on ingredients**

#### 3.2. Mixtures

Mixture contains these hazardous substances and substances with the highest permissible concentration in the working environment

Identification numbers	Substance name	Content in % weight	Classification according to Regulation (EC) No 1272/2008	Note
Index: 607-021-00-X CAS: 79-20-9 EC: 201-185-2	methyl acetate	≤49,0	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336 EUH066	
Index: 601-003-00-5 CAS: 74-98-6 EC: 200-827-9	propane	≤35,0	Flam. Gas 1, H220 Press. Gas (compressed gas), H280	3
Index: 601-004-00-0 CAS: 106-97-8 EC: 203-448-7	butane	≤15,0	Flam. Gas 1, H220 Press. Gas (compressed gas), H280	1, 3

**BIODUR**<sup>®</sup>

according to Commission Regulation (EU) 2020/878 as amended

### **BIODUR CONSTRUCTION MARKING SPRAY**

Creation	date
Revision	date

23rd March 2023

Version

1.0

Revision date		Version 1.0		
Identification numbers	Substance name	Content in % weight	Classification according to Regulation (EC) No 1272/2008	Note
Index: 607-025-00-1 CAS: 123-86-4 EC: 204-658-1	n-butyl acetate	≤4,0	Flam. Liq. 3, H226 STOT SE 3, H336 EUH066	4
Index: 607-035-00-6 CAS: 80-62-6 EC: 201-297-1	methyl methacrylate	<0.5	Flam. Liq. 2, H225 Skin Irrit. 2, H315 Skin Sens. 1, H317 STOT SE 3, H335	2, 4

Notes

- 1 Note C: Some organic substances may be marketed either in a specific isomeric form or as a mixture of several isomers. In this case the supplier must state on the label whether the substance is a specific isomer or a mixture of isomers.
- 2 Note D: Certain substances which are susceptible to spontaneous polymerisation or decomposition are generally placed on the market in a stabilised form. It is in this form that they are listed in Part 3 of Annex VI to Regulation (EC) No 1272/2008. However, such substances are sometimes placed on the market in a non-stabilised form. In this case, the supplier who places such a substance on the market must state on the label the name of the substance followed by the words "non-stabilised".
- 3 Note U (Table 3): When put on the market gases have to be classified as "Gases under pressure", in one of the groups compressed gas, liquefied gas, refrigerated liquefied gas or dissolved gas. The group depends on the physical state in which the gas is packaged and therefore has to be assigned case by case. The following codes are assigned:

Press. Gas (Comp.) Press. Gas (Liq.) Press. Gas (Ref. Liq.) Press. Gas (Diss.)

Aerosols shall not be classified as gases under pressure (See Annex I, Part 2, Section 2.3.2.1, Note 2).

4 A substance for which exposure limits are set.

Full text of all classifications and hazard statements is given in the section 16.

#### **SECTION 4: First aid measures**

#### 4.1. Description of first aid measures

If any health problems are manifested or if in doubt, inform a doctor and show him information from this safety data sheet.

#### If inhaled

Terminate the exposure immediately; move the affected person to fresh air. Protect the person against growing cold. Provide medical treatment if irritation, dyspnoea or other symptoms persist.

#### If on skin

Remove contaminated clothes. Wash the affected area with plenty of water, lukewarm if possible.

#### If in eyes

Rinse eyes immediately with a flow of running water, open the eyelids (also using force if needed); remove contact lenses immediately if worn by the affected person. Rinsing should continue at least for 10 minutes. Provide medical treatment, specialized if possible.

#### If swallowed

Unlikely.

#### 4.2. Most important symptoms and effects, both acute and delayed

If inhaled

May cause drowsiness or dizziness.

- If on skin
- Not expected.

If in eyes

Causes serious eye irritation. If swallowed

Irritation, nausea.

according to Commission Regulation (EU) 2020/878 as amended

### **BIODUR CONSTRUCTION MARKING SPRAY**

Creation date Revision date 23rd March 2023

Version

1.0

BIODUR®

**4.3.** Indication of any immediate medical attention and special treatment needed Symptomatic treatment.

Symptomatic treatment.

**SECTION 5: Firefighting measures** 

### 5.1. Extinguishing media

#### Suitable extinguishing media

Alcohol-resistant foam, carbon dioxide, powder, water spray jet, water mist.

#### Unsuitable extinguishing media

Water - full jet.

#### 5.2. Special hazards arising from the substance or mixture

In the event of fire, carbon monoxide, carbon dioxide and other toxic gases may arise. Inhalation of hazardous degradation (pyrolysis) products may cause serious health damage.

#### 5.3. Advice for firefighters

Self-Contained Breathing Apparatus (SCBA) with a chemical protection suit only where personal (close) contact is likely. Use a self-contained breathing apparatus and full-body protective clothing. Closed containers with the product near the fire should be cooled with water. Do not allow run-off of contaminated fire extinguishing material to enter drains or surface and ground water.

#### **SECTION 6: Accidental release measures**

#### 6.1. Personal precautions, protective equipment and emergency procedures

Provide sufficient ventilation. Pressurised container: May burst if heated. Extremely flammable aerosol. Remove all ignition sources. Use personal protective equipment for work. Follow the instructions in the Sections 7 and 8. Do not inhale aerosols. Prevent contact with skin and eyes.

### 6.2. Environmental precautions

Prevent contamination of the soil and entering surface or ground water.

#### 6.3. Methods and material for containment and cleaning up

Spilled product should be covered with suitable (non-flammable) absorbing material (sand, diatomaceous earth, earth and other suitable absorption materials); to be contained in well closed containers and removed as per the Section 13. In the event of leakage of the substantial amount of the product, inform fire brigade and other competent bodies. After removal of the product, wash the contaminated site with plenty of water. Do not use solvents.

#### 6.4. Reference to other sections

See the Section 7, 8 and 13.

#### SECTION 7: Handling and storage

#### 7.1. Precautions for safe handling

Prevent formation of gases and vapours in flammable or explosive concentrations and concentrations exceeding the occupational exposure limits. The product should be used only in the areas where it is not in contact with open fire and other ignition sources. Use non-sparking tools. Use of antistatic clothes and footwear is recommended. Do not inhale aerosols. Prevent contact with skin and eyes. No smoking. Protect against direct sunlight. Do not pierce or burn, even after use. Wash hands and exposed parts of the body thoroughly after handling. Do not spray on an open flame or other ignition source. Use only outdoors or in a well-ventilated area. Use personal protective equipment as per Section 8. Observe valid legal regulations on safety and health protection.

### 7.2. Conditions for safe storage, including any incompatibilities

Store in tightly closed containers in cold, dry and well ventilated areas designated for this purpose. Store locked up. Protect from sunlight. Keep container tightly closed. Do not expose to temperatures exceeding 50 °C.

Content	Packaging type	Material of package
500 ml	aerosol can	FE

### 7.3. Specific end use(s)

not available

#### SECTION 8: Exposure controls/personal protection

#### 8.1. Control parameters

The mixture contains substances for which occupational exposure limits are set.

**BIODUR**<sup>®</sup> according to Commission Regulation (EU) 2020/878 as amended

## **BIODUR CONSTRUCTION MARKING SPRAY**

Creation date Revision date 23rd March 2023

Version

1.0

Commission Directive 2009/161/FU

European Union	Commission	Commission Directive 2000/39/EC	
Substance name (component)	Туре	Value	
	OEL 8 hours	241 mg/m <sup>3</sup>	
n-butyl acetate (CAS: 123-86-4)	OEL 8 hours	50 ppm	
II-DULYI ACELALE (CAS: 123-80-4)	OEL 15 minutes	723 mg/m <sup>3</sup>	
	OEL 15 minutes	150 ppm	

### European Union

Substance name (component)	Type Value			
mathyl mathacrylate (CAS, 80,62,6)	OEL 8 hours 50 ppm			
methyl methacrylate (CAS: 80-62-6)	OEL 15 minutes 100 ppm			

#### 8.2. **Exposure controls**

Follow the usual measures intended for health protection at work and especially for good ventilation. This can be achieved only by local suction or efficient general ventilation. If exposure limits cannot be observed in this mode, suitable protection of airways must be used. Do not eat, drink and smoke during work. Wash your hands thoroughly with water and soap after work and before breaks for a meal and rest.

#### Eye/face protection

Protective goggles.

Skin protection

Hand protection: Protective gloves resistant to the product. Contaminated skin should be washed thoroughly.

#### **Respiratory protection**

Halfmask with a filter against organic vapours or a self-contained breathing apparatus as appropriate if exposure limit values of substances are exceeded or in a poorly ventilated environment.

Thermal hazard

#### Not available. **Environmental exposure controls**

Observe usual measures for protection of the environment, see Section 6.2.

#### **SECTION 9: Physical and chemical properties**

#### 9.1. Information on basic physical and chemical properties

Physical state	liquid
Colour	yellow, green, red, orange, pink, blue, wg asortymentu
Odour	data not available
Melting point/freezing point	data not available
Boiling point or initial boiling point and boiling range	data not available
Flammability	data not available
Lower and upper explosion limit	data not available
Flash point	data not available
Auto-ignition temperature	data not available
Decomposition temperature	data not available
рН	0 (undiluted)
Kinematic viscosity	data not available
Solubility in water	data not available
Partition coefficient n-octanol/water (log value)	data not available
Vapour pressure	data not available
Density and/or relative density	
Density	0,75-1,20 g/cm <sup>3</sup> at 20 °C
Relative vapour density	data not available
Particle characteristics	data not available
Other information	
VOC limit value	cat. A (d) SB: 300 g/l

9.2.

according to Commission Regulation (EU) 2020/878 as amended

# **BIODUR CONSTRUCTION MARKING SPRAY**

Creation date Revision date 23rd March 2023

Version

1.0

**BIODUR**<sup>®</sup>

#### **SECTION 10: Stability and reactivity**

#### 10.1. Reactivity

not available

### 10.2. Chemical stability

The product is stable under normal conditions.

**10.3.** Possibility of hazardous reactions Unknown.

#### 10.4. Conditions to avoid

The product is stable and no degradation occurs under normal use. Protect against flames, sparks, overheating and against frost. Pressurised container: May burst if heated.

#### 10.5. Incompatible materials

Protect against strong acids, bases and oxidizing agents.

#### 10.6. Hazardous decomposition products

Not developed under normal uses. Dangerous outcomes such as carbon monoxide and carbon dioxide are formed at high temperature and in fire.

#### **SECTION 11: Toxicological information**

#### 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Inhalation of solvent vapors above values exceeding exposure limits for working environment may result in acute inhalation poisoning, depending on the level of concentration and exposure time. No toxicological data is available for the mixture.

#### Acute toxicity

Based on available data the classification criteria are not met.

#### Skin corrosion/irritation

Based on available data the classification criteria are not met.

#### Serious eye damage/irritation

Causes serious eye irritation.

#### Respiratory or skin sensitisation

Based on available data the classification criteria are not met.

#### Germ cell mutagenicity

#### Carcinogenicity

Based on available data the classification criteria are not met.

#### **Reproductive toxicity**

Based on available data the classification criteria are not met.

#### Toxicity for specific target organ - single exposure

May cause drowsiness or dizziness.

#### Toxicity for specific target organ - repeated exposure

Based on available data the classification criteria are not met.

#### Aspiration hazard

Based on available data the classification criteria are not met.

#### 11.2. Information on other hazards

The mixture does not contain substances with endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605.

#### **SECTION 12: Ecological information**

#### 12.1. Toxicity

- Acute toxicity
- 12.2. Persistence and degradability not available
- 12.3. Bioaccumulative potential
- Not available.
- **12.4.** Mobility in soil Not available.
- 12.5. Results of PBT and vPvB assessment

according to Commission Regulation (EU) 2020/878 as amended

## **BIODUR CONSTRUCTION MARKING SPRAY**

Creation date Revision date 23rd March 2023

Version

1.0

**BIODUR**<sup>®</sup>

Product does not contain any substance meeting the criteria for PBT or vPvB in accordance with the Annex XIII of Regulation (EC) No 1907/2006 (REACH) as amended.

#### 12.6. Endocrine disrupting properties

The mixture does not contain substances with endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605.

# **12.7.** Other adverse effects Not available.

#### **SECTION 13: Disposal considerations**

#### 13.1. Waste treatment methods

Hazard of environmental contamination; dispose of the waste in accordance with the local and/or national regulations. Proceed in accordance with valid regulations on waste disposal. Any unused product and contaminated packaging should be put in labelled containers for waste collection and submitted for disposal to a person authorised for waste removal (a specialized company) that is entitled for such activity. Do not empty unused product in drainage systems. The product must not be disposed of with municipal waste. Empty containers may be used at waste incinerators to produce energy or deposited in a dump with appropriate classification. Perfectly cleaned containers can be submitted for recycling.

#### Waste management legislation

Directive 2008/98/EC of the European Parliament and of the Council of 19 November 2008 on waste, as amended. Decision 2000/532/EC establishing a list of wastes, as amended.

#### **SECTION 14: Transport information**

- 14.1. UN number or ID number
  - UN 1950
- **14.2.** UN proper shipping name AEROSOLS
- 14.3. Transport hazard class(es) 2 Gases
- **14.4.** Packing group not relevant

# 14.5. Environmental hazards not relevant

- **14.6.** Special precautions for user Reference in the Sections 4 to 8.
- 14.7. Maritime transport in bulk according to IMO instruments

## not relevant

### Additional information

Hazard identification No.

UN number Classification code Safety signs



**BIODUR**<sup>®</sup>

according to Commission Regulation (EU) 2020/878 as amended

## **BIODUR CONSTRUCTION MARKING SPRAY**

Creation date 23rd March 2023			
Revision date	Version	1.0	
Road transport - ADR			
Special provisions	190, 327, 344, 625		
Limited quantities	1 L		
Excepted quantities	EO		
Packaging			
Packing instructions	P207, LP200		
Special packing provisions	PP87, RR6, L2		
Mixed packing provisions	MP9		
Transport category	2		
Tunnel restriction code	(D/E)		
Special provision for			
packages	V14		
loading, unloading and handling	CV9, CV12		
operation	S2		
Railway transport - RID			
Special provisions	190, 327, 344, 625		
Excepted quantities	EO		
Packaging			
Packing instructions	P207, LP200		
Special packing provisions	PP87, RR6, L2		
Mixed packing provisions	MP9		
Transport category	0		
Special provision for			
packages	W 14		
loading, unloading and handling	CW 9, CW 12		
Air transport - ICAO/IATA			
Packaging instructions for limited amount	Y203		
Packaging instructions passenger	203		
Cargo packaging instructions	203		
Marine transport - IMDG			
EmS (emergency plan)	F-D, S-U		
MFAG	620		

#### **SECTION 15: Regulatory information**

#### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Regulation (EC) No. 1907/2006 of the European Parliament and of the Council of 18th December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing the European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No. 793/93 and Commission Regulation (EC) No. 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC, as amended. REGULATION (EC) No. 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL as amended. Commission Regulation (EU) 2020/878 of 18 June 2020 amending Annex II to Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH).

#### 15.2. Chemical safety assessment

not available

#### **SECTION 16: Other information**

A list of standard risk phrases used in the safety data sheet		
H220	Extremely flammable gas.	
H222	Extremely flammable aerosol.	
H225	Highly flammable liquid and vapour.	
H226	Flammable liquid and vapour.	
H229	Pressurised container: May burst if heated.	
H280	Contains gas under pressure; may explode if heated.	
H315	Causes skin irritation.	

**BIODUR**<sup>®</sup>

according to Commission Regulation (EU) 2020/878 as amended

# **BIODUR CONSTRUCTION MARKING SPRAY**

Creation date	23rd March 2023
Revision date	Version 1.0
H317	May cause an allergic skin reaction.
H317 H319	May cause an allergic skin reaction. Causes serious eye irritation.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
P101	afe handling used in the safety data sheet If medical advice is needed, have product container or label at hand.
P101 P102	Keep out of reach of children.
P102 P210	Keep out of reach of children. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources.
	No smoking.
P211	Do not spray on an open flame or other ignition source.
P251	Do not pierce or burn, even after use.
P410+P412	Protect from sunlight. Do no expose to temperatures exceeding 50 °C.
A list of addition EUH211	al standard phrases used in the safety data sheet Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.
EUH066	Repeated exposure may cause skin dryness or cracking.
	information about human health protection
The product must	not be - unless specifically approved by the manufacturer/importer - used for purposes other than 1. The user is responsible for adherence to all related health protection regulations.
	ions and acronyms used in the safety data sheet
ADR	European agreement concerning the international carriage of dangerous goods by road
BCF	Bioconcentration Factor
CAS	Chemical Abstracts Service
CLP	Regulation (EC) No 1272/2008 on classification, labelling and packaging of substance and mixtures
EC	Identification code for each substance listed in EINECS
EINECS	European Inventory of Existing Commercial Chemical Substances
EmS	Emergency plan
EU	European Union
EuPCS	European Product Categorisation System
IATA	International Air Transport Association
IBC	International Code For The Construction And Equipment of Ships Carrying Dangerous Chemicals
ICAO	International Civil Aviation Organization
IMDG	International Maritime Dangerous Goods
IMO	International Maritime Organization
INCI	International Nomenclature of Cosmetic Ingredients
ISO	International Organization for Standardization
IUPAC	International Union of Pure and Applied Chemistry
log Kow	Octanol-water partition coefficient
OEL	Occupational Exposure Limits
PBT	Persistent, Bioaccumulative and Toxic
ppm	Parts per million
Press. Gas (Comp	
Press. Gas (Diss.)	
Press. Gas (Liq.)	Gas under pressure: liquefied gas
Press. Gas (Ref. L	
REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals
RID	Agreement on the transport of dangerous goods by rail
UN	Four-figure identification number of the substance or article taken from the UN Model Regulations
UVCB	Substances of unknown or variable composition, complex reaction products or biological materials
VOC	Volatile organic compounds
vPvB	Very Persistent and very Bioaccumulative

**BIODUR**<sup>®</sup>

according to Commission Regulation (EU) 2020/878 as amended

# **BIODUR CONSTRUCTION MARKING SPRAY**

Creation date Revision date 23rd March 2023

Version

1.0

Aerosol	Aerosol
Eye Irrit.	Eye irritation
Flam. Gas	Flammable gas
Flam. Liq.	Flammable liquid
Press. Gas	Gases under pressure
Skin Irrit.	Skin irritation
Skin Sens.	Skin sensitization
STOT SE	Specific target organ toxicity - single exposure

#### Training guidelines

Inform the personnel about the recommended ways of use, mandatory protective equipment, first aid and prohibited ways of handling the product.

#### **Recommended restrictions of use**

not available

#### Information about data sources used to compile the Safety Data Sheet

REGULATION (EC) No. 1907/2006 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL (REACH) as amended. REGULATION (EC) No. 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL as amended. Data from the manufacturer of the substance / mixture, if available - information from registration dossiers.

#### More information

Classification procedure - calculation method.

#### Statement

The safety data sheet provides information aimed at ensuring safety and health protection at work and environmental protection. The provided information corresponds to the current status of knowledge and experience and complies with valid legal regulations. The information should not be understood as guaranteeing the suitability and usability of the product for a particular application.